



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS AND PATCHING

Other means of identification

Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Industries Limited
IDA Business & Technology Park
Ballynattin, Arklow,
Co. Wicklow
Ireland
Y14 A370
Tel : +353 (0)402 32370

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin irritation	Category 2 - (H315)
Serious eye damage	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	

2.2. Label elements

Contains Portland Cement

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING

Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01



Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P260 - Do not breathe dust

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, eye protection and face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P362 + P364 - Take off contaminated clothing and wash it before reuse

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can diminish prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Ireland - BE

Page 2 / 14

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Portland Cement 65997-15-1	>25 - <40	[5]	266-043-4	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	-
Cement, alumina, chemicals 65997-16-2	1 - <5	No data available	266-045-5	Eye Irrit. 2 (H319)	-	-	-	-
Disodium carbonate 497-19-8	0.1- <1	01-2119485498-19-XXXX	207-838-8 (011-005-00-2)	Eye Irrit. 2 (H319)	-	-	-	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-
Cement, alumina, chemicals	266-045-5	65997-16-2	-	-	-	-	-
Disodium carbonate	207-838-8 (011-005-00-2)	497-19-8	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. May cause blindness. May cause redness and tearing of the eyes. Itching. Rashes. Hives. Erythema (skin redness). Dust irritates eyes and air passages. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Sulphur oxides. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

6.3. Methods and material for containment and cleaning up

Methods for containment	Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.
Methods for cleaning up	Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Process mortar residues to let them harden, before returning the residues to recycling or disposing them according to applicable requirements.
Prevention of secondary hazards	Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation. Avoid generation of dust. Use personal protective equipment. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. For cements treated with a Cr (VI) reducing agent the effectiveness of the reducing agent diminishes with time and if not stored in an appropriate manner. After absorption of moisture or exceeding the shelf life the reducing agent for chromate will lose its efficiency and sensitisation by skin contact may occur.
---------------------------	--

7.3. Specific end use(s)

Specific use(s)
Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ ; total inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ (calculated); respira ble dust STEL: 7.2 mg/m ³ (calculated); respira	TWA: 6 mg/m ³ ; inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ ; inhalable dust STEL: 7.2 mg/m ³ ; respirable dust

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

		ble dust	
Portland Cement 65997-15-1	-	TWA: 1 mg/m ³ ; respirable fraction STEL: 3 mg/m ³ (calculated); respirable fraction	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Sulfuric acid, calcium salt (1:1) 7778-18-9	-	TWA: 10 mg/m ³ ; STEL: 30 mg/m ³ (calculated);	
Dust RR-12364-8	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Kaolin 1332-58-7	-	TWA: 2 mg/m ³ ; respirable dust	TWA: 2 mg/m ³ ; respirable dust STEL: 6 mg/m ³ ; respirable dust

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Portland Cement (65997-15-1)			
Disodium carbonate (497-19-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection

Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection

Avoid generation of dust. Possible nuisance dust. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Recommended filter type:

Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Colour	Grey
Odour	No information available.

Property	Values	Remarks • Method
Melting point / freezing point	. °C	Not applicable
Initial boiling point and boiling range	No data available	Not applicable
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	Not applicable
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	> 11	solution (25 %)
Kinematic viscosity	. mm ² /s	Not applicable
Dynamic viscosity	.	Not applicable
Water solubility	No data available. Cement based products react and solidify in contact with water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
Softening point	Not applicable
VOC content	No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available . Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

10.2. Chemical stability

Stability	Keep away from Incompatible materials. Stable under recommended storage conditions.
-----------	---

Explosion data

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supercedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/L
ATEmix (inhalation-vapour)	>20 mg/L

Component Information

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supercedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Portland Cement	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Cement, alumina, chemicals	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rattus	-
Disodium carbonate	=2800 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	= 2300 mg/m ³ (Rat) 2 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
---------------	----------------------	------	----------------------------	-----------	----------	----------------------

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Onchorhyncus mykiss) >100 mg/L (OECD 203)	-	EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)		
Disodium carbonate 497-19-8	EC50: =242mg/L (120h, Nitzschia)	LC50: =300mg/L (96h, Lepomis macrochirus) LC50: 310 - 1220mg/L (96h, Pimephales promelas)	-	EC50: =265mg/L (48h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Cement, alumina, chemicals	Not PBT/vPvB
Disodium carbonate	Not PBT/vPvB

12.6. Endocrine disrupting properties **Endocrine disrupting properties**

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects **Other adverse effects**

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
 10 13 06 particulates and dust (except 10 13 12 and 10 13 13)
 Cured product can be treated as construction waste. In the management of larger quantities consult with local authorities and local waste disposal company
 10 13 14 waste concrete and concrete sludge

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None
14.7 Maritime transport in bulk
according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING

Supersedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
U.S. EPA Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
U.S. National Institute for Occupational Safety and Health (NIOSH)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 08-May-2026

Revision Note SDS sections updated: 2

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

ARC POT-CEM RAPIDSET CEMENT FOR RAPID REPAIRS
AND PATCHING
Supercedes date 08-May-2026

Revision date 08-May-2026

Revision Number 1.01

End of Safety Data Sheet