



Issued 08/14

## CEILING PAINT

Dulux Ceiling Paint is a high quality Matt finish that splatters less than standard paint. It is specially formulated for ceilings, with excellent coverage and high opacity.. It is suitable for all normal interior ceiling surfaces but in conditions subject to frequent heavy condensation (e.g. some kitchens and bathrooms). Dulux Bathrooms or Trade Diamond Eggshell is more suitable.

### KEY BENEFITS

- High Opacity
- Splatter Resistant
- For Ceilings

### PRODUCT INFORMATION

#### Typical use

Suitable for all normal interior ceiling surfaces but in conditions subject to frequent heavy condensation (e.g. some kitchens and bathrooms). Dulux Bathrooms or Trade Diamond Eggshell is more suitable.

#### Pack Size

2.5L, 5L and 10L

#### Colour Range

See appropriate Dulux colour literature or visit [Dulux.ie](http://Dulux.ie)

#### Film Properties

Chemical Resistance: Not suitable

Heat Resistance: Not suitable for use on heated surfaces e.g. Radiators.

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments. Where frequent heavy condensation is likely, as in some kitchens and bathrooms, Dulux Bathrooms/Acrylic Eggshell is more suitable.

#### Composition (nominal)

Pigment: Lightfast Non-Lead Pigments

Binder: Acrylic Emulsion

Solvent: Water

#### Volume Solids

White 30% (nominal) other colours will vary.

### SURFACE PREPARATION

To get the best results with Dulux Ceiling Paint, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, greas and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate Polycell Trade Polyfilla.



## CEILING PAINT

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Dulux Ceiling Paint (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of Dulux Ceiling Paint, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient.

For the best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

### APPLICATION METHOD

Brush, Roller, Conventional Spray or Airless Spray.

As with other water-based paints, do not apply at temperatures below 7°C (as recommended by British Standard BS 6150).

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 13m<sup>2</sup> per litre.

#### Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 10 parts paint.

Normal Use (not to be exceeded): Add up to 1 part clean water to 10 parts paint (if required)

Conventional Spray: Add up to 1 part clean water to 5 parts paint.

Airless Spray: Thinning is not required

#### Spray Recommendations

Conventional Spray: Satisfactory through most equipment.

Airless Spray: A typical set up for airless spray would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size of 0.38mm (15 thou) and a spray tip angle of 65°.

#### Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4 Hours.

#### Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to Community RePaint. Find out more at [Dulux.ie](http://Dulux.ie)

#### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

#### VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 7 g/L VOC. VOC Content Low (0.30 – 7.99%).



Issued 08/14

## CEILING PAINT

### FURTHER SUPPORT

If you need further support, please contact the Dulux Technical Advice Centre on +353 21 422 0222

*Always read full Health, Safety & Environmental Information on can before use.*

Safety datasheet (SDS 411) is available free on request by telephoning the Dulux Technical Advice Centre or by visiting *dulux.ie*

Akzonobel the Akzonobel logo, the Flourish logo, Dulux Trade, Mouldshield, polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the Akzonobel group. © Akzonobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)

**AkzoNobel**