

Corrib Blocks

Corrib's smooth surface finish and refined bevelled edge make it a smart, stylish choice for your next project – delivering both visual appeal and functional performance.



Pedestrian
Use



Light
Traffic



Commercial
Traffic



Slip
Resistance



Factory Sealed
Available

Colour Profile




Silver Granite




Black Granite




Charcoal



Curragh Gold



Rustic



Slate

3D Profile



Features


- Offered with a choice of lightly textured or smooth surface finishes
- Available in an 80mm depth, suitable for commercial and heavy - duty applications
- Can be laid in a variety of patterns, depending on the selected unit size and shape
- Available in a range of six standard colours to suit most project requirements
- Custom colour options available on request for bespoke design needs.

Benefits

- Highly durable construction with enhanced cement and a robust granite surface finish
- Maintains consistently low slip resistance values over time - unlike natural granite or porcelain alternatives
- Significant cost savings on both supply and installation when compared to natural stone or porcelain options
- Factory - applied sealant now available on request, enhancing long - term performance and ease of maintenance



Sizing



210x170

Packaging Information

Dimensions (mm)	Colours	Pcs per m ²	m ² per Bale	Pcs per Bale	Pcs per Layer	No of Layers	Approx Bale Weight (kg)	Profile
210x170x50	Silver Granite, Black Granite, Charcoal, Curragh Gold, Rustic, Slate	28	11.18	313	24	13	1240	Chamfer
210x170x60	Silver Granite, Black Granite, Charcoal, Curragh Gold, Rustic, Slate	28	10.32	288	24	12	1384	Chamfer
210x170x80	Silver Granite, Black Granite, Charcoal, Curragh Gold, Rustic, Slate	28	6.88	192	24	8	1236	Chamfer

Technical Performance and Data

Product Type	Concrete Block Paving
Product Standard	EN 1338:2003
Manufacturing Method	Hydraulically pressed semi - dry concrete
Finish	Textured Granite Aggregate or Standard Smooth Finish
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	Extremely low - USRV / PTV above 75, as per EU 1339:2003 Table NA.4
Strength	Typically tensile splitting strength of > 3.6 MPa and a failure load of > 250N/ mm
Application & Trafficking	Product suitable for both pedestrian traffic & may be suitable for vehicular traffic when designed and installed in conjunction with the correct, site - specific sub - base as per the relevant BS7533 standard depending on the product size & depth
Joint	Corrib Block Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining
BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub - base.