

Kilsaran

KPRO FLOOR

Introducing our New LevelEase Range

Your Complete Flooring Solution



LevelEase 250

A rapid hardening and fibre reinforced cementitious levelling compound for use in domestic and commercial applications, over a multitude of substrate. Laying depth 2mm-50mm. CT-C30-F7.



LevelEase 225

A standard-setting and fibre-reinforced cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase Duo 225

A standard-setting two component cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase Sealing Primer

A high-performance, deep-penetrating primer designed to strengthen absorbent substrates and improve adhesion for subsequent layers. It ensures reduced absorbency and enhanced workability for a wide range of surface preparation tasks.



LevelEase Gritty Primer

A quartz infused, high-performance and fast-setting bonding primer which delivers a textured, gritty finish that significantly enhances the adhesion of subsequent layers, to smooth non-absorbent substrates.



LevelEase DPM

A one-component, water-based residual moisture vapor suppressant, designed to suppress residual construction moisture in cementitious substrates, where the moisture content is up to 95% RH.

Get in touch:
ROI: T: 01 801 3484 www.kilsaran.ie | **UK:** T: 0161 872 8899 www.kilsaraninternational.co.uk
Place an Order: orders@kilsaran.ie **Customer Service:** csteam@kilsaran.ie
Tech Support: techsupport@kilsaran.ie



Kilsaran

KPRO FLOOR



		LevelEase 250	LevelEase 225	LevelEase Duo 225
Laying Dept		2mm – 50mm	2mm – 25mm	2mm – 25mm
Suitability of substrates	**Concrete**	•••	••	••
	Plywood*	•••	O	O
	S&C Screed	•••	••	••
	Calcium Sulphate Screed	•••	••	••
	Ceramic Tiles	•••	••	••
Substrate preparation	**LevelEase Sealing Primer**	Required	Required	Required
	LevelEase Gritty Primer	Required on tiled substrates	Required on tiled substrates	Required on tiled substrates
	LevelEase DPM	If substrate moisture is ≥75% RH, ≤ 95%RH	If substrate moisture is ≥75% RH, ≤ 95%RH	If substrate moisture is ≥75% RH, ≤ 95%RH
Open to foot traffic		2 hours	4 hours	4 hours
Installation of floor coverings	**Tiles**	6 hours	12 hors	12 hours
	Resilient Coverings	24 hours	24 hours	24 hours

* Suitability of Substrates: ••• Ideal •• Suitable o Not Suitable

Get in touch:
ROI: T: 01 801 3484 www.kilsaran.ie | **UK:** T: 0161 872 8899 www.kilsaraninternational.co.uk
Place an Order: orders@kilsaran.ie **Customer Service:** csteam@kilsaran.ie
Tech Support: techsupport@kilsaran.ie