

Lismore Blocks

A contemporary range with sharp lines and a smooth surface finish make Lismore a stylish addition to any design concept.



Pedestrian
Use



Light
Traffic



Slip
Resistance



Factory Sealed
Available


Colour Profile




Natural




Raven



Ash Grey



Curragh Gold



Rustic

3D Profile




Features

- Durable concrete block paving design for long - term performance
- Lightly textured surface finish incorporating premium granite aggregates for a refined appearance
- Available in multiple depths to suit a range of traffic load requirements
- Modern square - edge design with flexible laying pattern options
- Offered in five standard colours and bespoke colours options available on request
- Typically supplied in a three - size mix to enhance visual appeal and design versatility

Benefits

- Exceptional durability due to increased cement content and a premium aggregate surface
- Maintains consistently low slip potential throughout its lifecycle - enhancing safety in both residential and commercial applications
- More cost-effective to supply and install than natural stone paving or porcelain alternatives
- Optional factory - applied surface sealant available on request for added protection and reduced maintenance

Sizing



120x160



160x160



240x160

Packaging Information

Dimensions (mm)	Colours	Pcs per m ²	m ² per Bale	Pcs per Bale	Pcs per Layer	No of Layers	Approx Bale Weight (kg)	Profile
3-size 50 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	11.52	420	35	12	1280	Each layer consists of 10 large, 15 med, 10 small - Square Edge
3-size 60 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	9.6	350	35	10	1303	Each layer consists of 10 Large, 15 med, 10 small - Square Edge
3-size 80 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	6.72	245	35	7	1194	Each layer consists of 10 Large, 15 med, 10 small - Square Edge

Technical Performance Data

Product Type	Concrete Block Paving
Product Standard	EN 1338:2003
Manufacturing Method	Hydraulically pressed semi - dry concrete
Finish	Standard Finish
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	Extremely low - Typically USRV / PTV > 75
Strength	Typically tensile splitting strength of > 3.6 MPa and a failure load of > 250N/ mm
Joint	Product suitable for both pedestrian, vehicular traffic when installation in conjunction with the correct, site specific sub - base design.
Application & Trafficking	Lismore Block Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining
BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub - base.