

Mellifont Blocks

With its edges and surface gently worn, Mellifont is ideal when creating an aged look.



Pedestrian
Use



Light
Traffic



Commercial
Traffic



Eco
Range



Slip
Resistance



Factory Sealed
Available

Colour Profile



Natural



Raven



Ash Grey



Curragh Gold



Rustic

3D Profile




Features

- Durable concrete block paving with a traditional, time - worn aesthetic
- Antiqued edges and textured surface replicate the appearance of aged cobbles
- Available in multiple depth to accommodate various traffic loadings
- Typically supplied in a three - size mix to enhance visual interest and design flexibility
- Compatible with a variety of laying patterns depending on selected unit sizes
- Offered in five standard colours, with bespoke colour options available upon request


Benefits

- Exceptional durability due to the increased cement content and a premium aggregate surface
- Maintains consistently low slip potential throughout it's lifecycle - enhancing safety in both residential and commercial applications
- More cost - effective to supply and install than natural stone paving or porcelain alternatives
- Optional factory - applied surface sealant available on request for added protection and reduced maintenance

Sizing



120x160



160x160



240x160

3-size mixed pack. Unit sizes and quantities per layer, as supplied.

Packaging Information

Dimensions (mm)	Colours	Pcs per m ²	m ² per Bale	Pcs per Bale	Pcs per Layer	No of Layers	Approx Bale Weight (kg)	Profile
3-size 50 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	11.52	420	35	12	1280	Each layer consists of 10 large, 15 med, 10 small - Antiqued
3-size 60 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	9.60	350	35	10	1303	Each layer consists of 10 Large, 15 med, 10 small - Antiqued
3-size 80 (120x160) (160x160) (240x160)	Natural, Raven, Curragh Gold, Ash Grey, Rustic	N/A	6.72	245	35	7	11934	Each layer consists of 10 Large, 15 med, 10 small - Antiqued

Technical Performance and Data

Product Type	Concrete Block Paving
Product Standard	EN 1338:2003
Manufacturing Method	Hydraulically pressed semi - dry concrete
Finish	Mechanically distressed finish (Antiqued)
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	Extremely low - Typically USRV / PTV > 75
Strength	Typically tensile splitting strength of > 3.6 MPa and a failure load of > 250N/ mm
Application & Trafficking	Product suitable for both pedestrian, vehicular traffic when installation in conjunction with the correct, site specific sub- base design.
Joint	Mellifont Block Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining
BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub - base.